

K-TYPE PRECISION GROUND MILLING VISES

- Ground surface of a. top and bottom of vise bed. b. moveable jaw and jaw base. c. gib piece of moveable jaw d. All plate mounting surface.
- Jaw plates of hardened and ground tool steel, Bearing portion of Acme threaded lead screw stock is ground for accurate alignment.
- Body,moveable jaw and swivel base made of high tensile cast iron.
- Stress-relieved by annealing. Built for heavy duty machining and retained accuracy.
- Bronze Bushings for longer life.



CODE No.	Size	Jaw Width	Jaw Depth	Opening of Jaws	Net Weight
7000-0104	100 mm (4")	100 mm (4")	32 mm (1-1/8")	65 mm (2-9/16")	10 kgs (22 Lbs)
7000-0105	125 mm (5")	125 mm (5")	34 mm (1-1/2")	85 mm (3-1/8")	16 kgs (41.8 Lbs)
7000-0106	160 mm (6")	150 mm (6")	40 mm (1-5/8")	110 mm (4-1/2")	28 kgs (60 Lbs)
7000-0107	160 mm (6")	150 mm (6")	40 mm (1-5/8")	155 mm (6")	35 kgs (71 Lbs)
7000-0108	200 mm (8")	200 mm (8")	58 mm (2-1/4")	155 mm (6")	54 kgs (119 Lbs)