

TIGHT-LOCK PRECISION MILLING MACHINE VISES

- The vise bed is made of ductile cast iron which resists deflection bending.
- Flame hardened bed for wear resistance.
- Hardened and ground jaw plate.
- Ground surface top and bottom of vise bed, top of both jaw in pairs, all jaw plate mounting surfaces.
- Needle bearing of thrust collar, cuts friction and adds clamping power
- The swivel base is graduated 360 degree.
- Swevel handle.

CODE No.	Jaw Width	Jaw Height	Max.Opening	Overall Height	Net Weight
7000-0004	100 mm (4")	31 mm (1-1/8")	100 mm (4")	85 mm (3-3/8")	21 kgs (46 Lbs)
7000-0005	125 mm (5")	33 mm (1-5/16")	108 mm (4-1/4")	87 mm (3-13/16")	33 kgs (72.7 Lbs)
7000-0006	160 mm (6")	38 mm (1-1/2")	167 mm (6-1/4")	110 mm (4-3/8")	50 kgs (110 Lbs)
7000-1006	160 mm (6")	42 mm (1-5/8")	198 mm (7-7/8")	114 mm (4-1/2")	52 kgs (115 Lbs)
7000-0008	200 mm (8")	50 mm (2")	201 mm (7-1/2")	130 mm (5-5/16")	110 kgs (242 Lbs)